





## **Product Overview**

Excel Category 5e Unscreened Cables are manufactured and tested to the ISO 11801, EN 50173 and ANSI/TIA-568-C standards for enhanced performance Category 5 cables. Each cable consists of 8 colour coded polyethylene insulated conductors. These are twisted together to form 4 pairs with varying lay lengths.

The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

### **Product Specifications**


| Feature   | Values |
|---|--------|
| Category  | 5E     |
| Overall screening   | None   |
| Conductor screening   | None   |
| Outer sheath colour   | Violet |
| Reaction-to-fire class according to EN 13501-6                | Dca    |
| Smoke development class according to EN 13501-6               | s2     |
| Euro class flaming droplets/particles according to EN 13501-6 | N d2   |
| Euro class acidity according to EN 13501-6                    | a2     |
| AWG-size  | 24     |
| Specification core insulation                                 | PE     |
| Core identification   | Colour |
|   |        |



Item Code: 100-066

| Outer sheath material            | Copolymer                                    |
|----------------------------------|--|
| Halogen free (acc. EN 60754-1/2) | Yes  |
| Flame retardant                  | In accordance with EN 60332-1-2 and EN 50399 |
| Low smoke (acc. BS EN 61034-2)   | Yes  |
| Outer diameter approx.           | 5.2 mm                                       |
| Operating Temperature Range      | -2060 °C                                     |
| NVP value                        | 70 %   |
| Conductor category               | Class $1 = $ solid                           |
| Total number of cores            | 8  |
| Stranding element                | Pairs  |
| Conductor surface                | Bare   |

# **Cross-section diagram**



## **Cable specifications**

| Features                | Values       |
|-------------------------|--------------|
| Dielectric strength     | 2.5kV for 2s |
| Maximum Pulling Load    | 60N/6.1KgF   |
| MBR during installation | 8x cable OD  |
| MBR installed           | 4x cable OD  |



### Standards

| Applicable standard            | Subject   |
|--------------------------------|---|
| ISO/IEC 11801-1:2017           | Information technology - Generic cabling for customer premises: Part 1 General Requirements   |
| IEC 61156-5:2009+AMD1:2012 CSV | Multicore and symmetrical pair/quad cables for digital<br>communications - Part 5: Symmetrical pair/quad cables<br>with transmission characteristics up to 1 000 MHz -<br>Horizontal floor wiring - Sectional specification |
| EN 50173-1:2011                | Information technology. Generic cabling systems -<br>General requirements   |
| EN 50173-2:2007 + A1:2010      | Information technology. Generic cabling systems - Office<br>premises  |
| BS EN 50288-6-1:2013           | Multi-element metallic cables used in analogue and digital communication and control. Sectional specification for unscreened cables characterised up to 250 MHz   |
| EN 50399:2011+A1:2016          | Common test methods for cables under fire conditions.<br>Heat release and smoke production measurement on<br>cables during flame spread test. Test apparatus,<br>procedures, results  |
| IEC 60332-1-2:2004             | Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame  |
| ANSI/TIA 568-2.D               | Balanced Twisted-Pair Telecommunications Cabling and<br>Components Standards  |
| IEC 60754-2:2011               | Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity  |
| IEC 61034-2:2005+A1:2013       | Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements   |
| EN 50575:2014 + A1:2016        | Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements  |
| RoHS                           | Restriction of Hazardous Substances - Compliant   |
|                                |   |



### **Part Number Table**

| Part Number | Description   |
|-------------|---|
| 100-057     | Excel Category 5E Cable U/UTP Dca LS0H 305m Box - Orange      |
| 100-059     | Excel Category 5E Cable U/UTP Eca PVC 500m Reel - Grey        |
| 100-060     | Excel Category 5E Cable U/UTP Dca LS0H 305m Box - White       |
| 100-061     | Excel Category 5E Cable U/UTP Dca LS0H 305m Box - Red         |
| 100-062     | Excel Category 5E Cable U/UTP Dca LS0H 305m Box - Blue        |
| 100-063     | Excel Category 5E Cable U/UTP Dca LS0H 305m Box - Green       |
| 100-064     | Excel Category 5E Cable U/UTP Dca LS0H 305m Box - Yellow      |
| 100-066     | Excel Category 5E Cable U/UTP Dca LS0H 305m Box - Violet      |
| 100-102     | Excel Category 5E Dual Cable U/UTP Eca LS0H 500m Reel - White |
| 170-066     | Excel Category 5E Cable U/UTP Cca LS0H 305m Box - Violet      |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.