Excel 6-way Horizontal PDU - 6x UK sockets, C14 plug - Switched

Item Code: 555-250







- X IEC 60320 C13 style sockets
- X High quality, light weight aluminium housing
- X LED indicated unit power
- X Choose from vertical and horizontal mounting options
- × 250 volt AC, 50/60Hz Rating
- X CE compliant, ROHS complaint

Product Overview

Excel range of power distribution units are designed for installation and use within 19" networking cabinets and enclosures. Each unit comprises a high quality aluminium extruded housing into which are loaded up to 12 sockets.

The 10 Amp PDUs benefit from having a master power switch.

Product Specifications

| Feature | Values |
|----------------------------------|---------------------------|
| Mounting dimension | 19 inch |
| Mounting direction | Horizontal |
| Electrical connection | Connecting cord with plug |
| Type of electric plug connection | C14 |
| Cable length | 3 m |
| Number of UK BS1363 sockets | 6 |
| Number of rack units (RU) | 2 |
| Width | 482.6 mm |
| Height | 62 mm |
| Depth | 45 mm |

Excel 6-way Horizontal PDU - 6x UK sockets, C14 plug - Switched

Item Code: 555-250



| Supply voltage | 250 V |
|-----------------------|-------|
| Switchable | Yes |
| With LED indication | Yes |
| With mounting bracket | Yes |

Additional specifications


| Features | Values |
|---------------------------------------|-------------------------------------|
| Rated Voltage | 250 V AC 50/60 Hz |
| Rated current | 10A |
| Maximum power | 2500 W |
| Unit control | LED indicator. On/off rocker switch |
| Insulation Resistance | ≥5MΩ |
| Fire resistance | Flame retardant |
| Operating temperature | -10°C to +45°C |
| Relative humidity | 0% to 90% |
| Cable entry (horizontal orientation) | Left |
| Cable entry (vertical orientation) | Тор |
| Socket angle (horizontal orientation) | 90° |
| Socket angle (vertical orientation) | 45° |
| Master Switch | Yes |
| Housing colour | Silver |
| Housing material | Aluminum |

Excel 6-way Horizontal PDU - 6x UK sockets, C14 plug - Switched

Item Code: 555-250



Product drawing



| Key | |
|------|------------------|
| Α | Height |
| В | Width |
| С | Depth |
| .D . | Mounting Centres |

All dimensions are in mm unless stated otherwise

Standards

| Applicable standard | Detail |
|--|---|
| RoHS | Restriction of Hazardous Substances - Compliant |
| BS 1363-2:1995 | 13 A plugs, socket-outlets, adaptors and connection units. Specification for 13 A switched and unswitched socket- outlets |
| IEC 60884-1:2002 + AMD1:2006 + AMD2:2013 CSV | Plugs and socket-outlets for household and similar purposes - Part1: General requirements |

Part Number Table

| Part Number | Description |
|-------------|---|
| 555-250 | Excel 6-way Horizontal PDU - 6x UK sockets, C14 plug - Switched |
| 555-251 | Excel 8-way Vertical PDU - 8x UK sockets, C14 plug - Switched |
| 555-252 | Excel 10-way Vertical PDU - 10x UK sockets, C14 plug - Switched |
| 555-253 | Excel 12-way Vertical PDU - 12x UK sockets, C14 plug - Switched |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.