Item Code: 100-011









- X Supports Gigabit Ethernet
- X IDC point at 90° to jack
- X Choice of colour
- X Mounts in shutter
- X 3P Verified
- 25 Year system warranty

Product Overview

Excel Keystone jack outlets provide an alternative to the one piece shuttered module range. Suitable for mounting in a range of faceplates or shutters, these jacks are quick and easy to install.

Product Specifications

| Feature | Values |
|---------------------------|--------------------|
| Model | Jack |
| Type of connector | RJ45 8(8) |
| Category | 6 |
| Connection type | 110 |
| Requires termination tool | 110 Punchdown tool |
| Suitable for round cable | Yes |
| Suitable for solid core | Yes |
| Colour | White |
| AWG-range | 2226 |

Item Code: 100-011



Additional specifications


| Features | Values |
|---------------------------------|---|
| Width | 16.5mm |
| Depth | 30.9mm |
| Height | 19.2mm |
| Housing | ABS High-Impact |
| RJ45 Contacts | Nickel plated phosphor bronze alloy with 50 micro-inch Gold plating |
| IDC Contacts | Tin plated phosphor bronze alloy |
| RJ45 Life | Minimum 750 insertions |
| Contact force | 100 grams with FCC compliant RJ-45 plug |
| Plug retention | 48.9 N |
| Suitable impact tool | 110 style punch down tool |
| Storage temprature | -40 to +70°C |
| Operating temprature | -10 to +60°C |
| Relative humidity (Operational) | 10% to 90% RH |


Item Code: 100-011




Product drawing

Side View







Bottom View









Included accessories

| Accessories | Quantity |
|-----------------|----------|
| Nylon cable tie | 1 |
| Wiring cap | 1 |

Standards

| Applicable standard | Detail |
|----------------------|--|
| RoHS | Restriction of Hazardous Substances - Compliant |
| ISO/IEC 11801-1:2017 | Information technology - Generic cabling for customer premises: Part 1 General Requirements |
| EN 50173-1:2011 | Information technology. Generic cabling systems - General requirements |
| ANSI/TIA 568-2.D | Balanced Twisted-Pair Telecommunications Cabling and Components Standards |
| UL-94-V-0 | Burning stops within 10 seconds after two applications of ten seconds each of a flame to a test bar. NO flaming drips are allowed. |

Item Code: 100-011



Part Number Table

| Part Number | Description |
|---------------|---|
| 100-011 | Excel Category 6 (UTP) Unscreened Keystone Jack - White |
| 100-011-24 | Excel Category 6 (UTP) Unscreened Keystone Jack - White (24-pack) |
| 100-011-BK | Excel Category 6 (UTP) Unscreened Keystone Jack - Black |
| 100-011-BK-24 | Excel Category 6 (UTP) Unscreened Keystone Jack - Black (24-pack) |
| 100-011-BU | Excel Category 6 (UTP) Unscreened Keystone Jack - Blue |
| 100-011-GN | Excel Category 6 (UTP) Unscreened Keystone Jack - Green |
| 100-011-RD | Excel Category 6 (UTP) Unscreened Keystone Jack - Red |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

